§ 117.72

- (d) Cork and balsa wood life jackets previously approved in accordance with §§ 106.003, or 160.004 in subchapter Q of this chapter, on board an existing vessel prior to March 11, 1996, may continue to be used to meet the requirements of this section until March 11, 1999, provided the life jackets are maintained in good and serviceable condition.
- (e) Each life jacket carried on board the vessel must be marked in accordance with §122.604 of this chapter.

[CGD 85-080, 61 FR 911, Jan. 10, 1996, as amended by CGD 97-057, 62 FR 51047, Sept. 30, 1997; CGD 85-080, 62 FR 51350, Sept. 30, 1997]

§ 117.72 Personal flotation devices carried in addition to life jackets.

- (a) Equipment carried under this section is not acceptable in lieu of any portion of the required number of approved life jackets and must not be substituted for the approved life jackets required to be worn during drills and emergencies.
- (b) Wearable marine buoyant devices that include "ski vests," "boating vests," and "fishing vests," approved in accordance with \$160.064 in subchapter Q of this chapter, or other standard specified by the Commandant, may be carried as additional equipment.
- (c) Buoyant work vests approved in accordance with §160.053 in subchapter Q of this chapter, or other standard specified by the Commandant, may be carried as additional equipment for use of persons working near or over the water.
- (d) Commercial hybrid personal flotation devices (PFD) approved in accordance with §160.077 in subchapter Q of this chapter, or other standard specified by the Commandant, may be carried as additional equipment for use of persons working near or over the water. Each commercial hybrid PFD must be:
- (1) Used, stowed, and maintained in accordance with the procedures set out in the manual required for these devices under §160.077-29 in subchapter Q of this chapter and any limitation(s) marked on them; and
- (2) Of the same or smaller design and have the same method of operation as

each other hybrid PFD carried on board

§117.75 Life jacket lights.

- (a) Each life jacket carried on a vessel on an oceans, coastwise, or Great Lakes route, must have a life jacket light approved in accordance with Subpart 161.012 of this chapter. Each life jacket light must be securely attached to the front shoulder area of the life jacket.
- (b) Notwithstanding the requirements of paragraph (a) of this section, life jacket lights are not required for life jackets on:
 - (1) Ferries; and
- (2) Vessels with Certificates of Inspection endorsed only for routes that do not extend more than 20 miles from a harbor of safe refuge.

§117.78 Stowage of life jackets.

- (a) *General*. Unless otherwise stated in this section, life jackets must be stored in convenient places distributed throughout accommodation spaces.
- (1) Each stowage container for life jackets must not be capable of being locked. If practicable, the container must be designed to allow the life jackets to float free.
- (2) Each life jacket kept in a stowage container must be readily available.
- (3) Each life jacket stowed overhead must be supported in a manner that allows quick release for distribution.
- (4) If life jackets are stowed more than 2,130 millimeters (7 feet) above the deck, a means for quick release must be provided and must be capable of operation by a person standing on the deck
- (5) Each child size life jacket must be stowed in a location that is appropriately marked and separated from adult life jackets so the child size life jackets are not mistaken for adult life jackets.
- (b) Additional personal flotation devices. The stowage locations of the personal flotation devices carried in addition to life jackets under §117.72 must be separate from the life jackets, and such as not to be easily confused with that of the life jackets.